


## EVT007

ADOAH043VAS0005E04

Connection technology



### Product characteristics

Socket

For sensors with

M12 connector

Free from silicone

gold-plated contacts

For hygienic and wet areas in the food industry

### Electrical data

Electrical design		DC PNP
Operating voltage	[V]	10...36 DC
Current rating	[A]	4
Protection class		II

### Environment

Ambient temperature	[°C]	-25...100, cULus: max. 50 °C
Ambient temperature (moving)	[°C]	5...100, cULus: max. 50 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

### Tests / approvals

MTTF	[Years]	20027
------	---------	-------

### Mechanical data

Design		angled
Material body		housing: PVC black transparent; sealing: EPDM
Material nut		stainless steel 316L / 1.4404
Tightening torque for knurled nut [Nm]		0.6...1.5
Drag chain suitability		<p>Bending radius for flexible applications:</p> <p>min. 10 x cable diameter max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s<sup>2</sup></p> <p>Travel speed: 5 m/s<sup>2</sup></p> <p>Bending cycles: &gt; 1 million</p> <p>Torsional strain: ± 180 °/m</p>
Weight	[kg]	0.192

### Displays / operating elements

Output status indication	LED	2 x yellow
Power	LED	green

### Electrical connection

Connection		PVC cable / 5 m; 4 x 0.34 mm <sup>2</sup> (42 x Ø 0.1 mm); Ø 4.9 mm
Sheath color		orange



## EVT007



ADOAH043VAS0005E04

Connection technology

### Wiring

Core colors

BK black  
BN brown  
BU blue  
WH white



### Remarks

Pack quantity [piece] 1