

ORDERING INFORMATION				
GAUGE SIZES	15 1-1/2"	20 2"	25 2-1/2"	40 4"
CASE TYPES	900 ABS Case, bottom connection 901 SS Case, bottom connection		910 ABS Case, back connection 911 SS Case, back connection	
PRESSURE RANGES	30vac -30 inHg to 0 psi 30/15 -30 inHg to 0 to 15 psi 30/30 -30 inHg to 0 to 30 psi 30/60 -30 inHg to 0 to 60 psi 30/100 -30 inHg to 0 to 100 psi 30/160 -30 inHg to 0 to 160 psi 30/200 -30 inHg to 0 to 200 psi 30/300 -30 inHg to 0 to 300 psi 15 0 psi to 15 psi 30 0 psi to 30 psi 60 0 psi to 60 psi	100 0 psi to 100 psi 160 0 psi to 160 psi 200 0 psi to 200 psi 300 0 psi to 300 psi 400 0 psi to 400 psi 600 0 psi to 600 psi 800 0 psi to 800 psi 1000 0 psi to 1,000 psi 1500 0 psi to 1,500 psi 2000 0 psi to 2,000 psi 3000 0 psi to 3,000 psi	5000 0 psi to 5,000 psi 6000 0 psi to 6,000 psi 7500 0 psi to 7,500 psi 10000 0 psi to 10,000 psi 15000 0 psi to 15,000 psi -1 -1 bar to 0 bar 1 0 bar to 1 bar 1.6 0 bar to 1.6 bar 2.5 0 bar to 2.5 bar 4 0 bar to 4 bar 6 0 bar to 6 bar	10 0 bar to 10 bar 16 0 bar to 16 bar 25 0 bar to 25 bar 40 0 bar to 40 bar 60 0 bar to 60 bar 100 0 bar to 100 bar 160 0 bar to 160 bar 250 0 bar to 250 bar 400 0 bar to 400 bar 600 0 bar to 600 bar 1000 0 bar to 1,000 bar
SCALE OPTIONS	psi psi single scale psi/bar psi/bar dual scale	psi/kg/cm <sup>2</sup> psi/kg/cm <sup>2</sup> dual scale	bar/psi bar/psi dual scale	psi/kPa psi/kPa dual scale
CONNECTION SIZES	1/8 1/8" NPT	1/4 1/4" NPT	1/2 1/2" NPT	SST SAE J1926-3:7/16-20 Adjustable*
OPTIONS	PMC Steel Panel Mount Clamp SPMC 304SS Panel Mount Clamp SSBU Stainless Steel Bezel & U-clamp SSB Stainless Steel Bezel SSCR 304SS Cover Ring	AP Adjustable Pointer MIP Maximum Indicating Pointer SP Red Set Pointer SG Safety Glass Lens BLFF Black Front Flange	SSFF 304SS Front Flange SSRF 304SS Rear Flange LM Laser Marking ST Stainless Steel Tagging	BP3 Brass Press Fit Orifice 0.3 mm BT5 Brass Threaded Orifice 0.5 mm BT8 Brass Threaded Orifice 0.8 mm

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

NOTE: Refer to 900 Series Options & Accessories chart on page 53 for availability by series number.

\* Includes FKM o-ring

**EXAMPLE**

